

Chair for Network Architectures and Services Institute of Informatics TU München – Prof. Carle

# **Network Security**

Chapter 6 Random Number Generation for Cryptographic **Protocols** 



# **Motivation**

- It is crucial to security that cryptographic keys are generated with a truly random or at least a pseudo-random generation process (see subsequently)
- Otherwise, an attacker might reproduce the key generation process and easily find the key used to secure a specific communication
- Generation of pseudo-random numbers is required in cryptographic protocols for the generation of
  - Cryptographic keys
  - Nonces (Numbers Used Once)
- □ Example usages
  - Key generation and peer authentication in IPSec and SSL
  - Authentication with challenge-response-mechanism, e.g. GSM and UMTS authentication

Network Security, WS 2008/09, Chapter 6

# **Random Number Generators**

### Definition:

A random bit generator is a device or algorithm which outputs a sequence of statistically independent and unbiased binary digits.

- Remark:
  - A random bit generator can be used to generate uniformly distributed random numbers
  - e.g. a random integer in the interval [0, n] can be obtained by generating a random bit sequence of length  $\lfloor lg_2 n \rfloor + 1$  and converting it into a number.
  - If the resulting integer exceeds n it can be discarded and the process is repeated until an integer in the desired range has been generated.



# Entropy

(c.f. Niels Ferguson, Bruce Schneier: Practical Cryptography, pp. 155ff)

- □ The measure for "randomness" is called "entropy"
- Let X a random variable which outputs a sequence of n bits
- The Shannon information entropy is defined by:

$$H(X) = -\sum P(X = x) \ln_2(P(X = x))$$

□ E.g. if all possible outputs are equally probable, then

$$H(X) = -\sum_{i=0}^{2^{n}-1} \left(\frac{1}{2^{n}}\right) \ln_{2}\left(\frac{1}{2^{n}}\right) = -2^{n} * \frac{1}{2^{n}} * (-n) = n$$

- □ A secure cryptographic key of length *n* bits should have *n* bits of entropy.
- □ If k from the n bits become known to an attacker and the attacker has no information about the remaining (n - k) bits, then the key has an entropy of (n-k) bits
- □ A bits sequence of arbitrary large length that takes only 4 different values has only 2 bits of entropy
- Passwords that can be remembered by human beings have usually a much lower entropy than their length.
- □ Entropy can be understood as the average number of bits required to specify a bit-sequence if an ideal compression algorithm is used.



# **Pseudo-Random Number Generators (1)**

#### Definition:

- A pseudo-random bit generator (PRBG) is a deterministic algorithm which, given a truly random binary sequence of length k ("seed"), outputs a binary sequence of length m >> k which "appears" to be random.
- The input to the PRBG is called the *seed* and the output is called a *pseudo-random bit sequence*.

#### Remarks:

- The output of a PRBG is not random, in fact the number of possible output sequences of length *m* with 2<sup>k</sup> sequences is at most a small fraction of 2<sup>m</sup>, as the PRBG produces always the same output sequence for one (fixed) seed
- The motivation for using a PRBG is that it is generally too expensive to
  produce true random numbers of length *m*, e.g. by coin flipping, so just a
  smaller amount of random bits is produced and then a pseudo-random bit
  sequence is produced out of the *k* truly random bits
- In order to gain confidence in the "randomness" of a pseudo-random sequence, statistical tests are conducted on the produced sequences

Network Security, WS 2008/09, Chapter 6

### Random and Pseudo-Random Number Generation (3)

- Security requirements of PRBGs for use in cryptography:
  - As a minimum security requirement the length k of the seed to a PRBG should be large enough to make brute-force search over all seeds infeasible for an attacker
  - The output of a PRBG should be statistically indistinguishable from truly random sequences
  - The output bits should be unpredictable for an attacker with limited resources, if he does not know the seed

#### Definition:

A PRBG is said *to pass all polynomial-time statistical tests*, if no polynomial-time algorithm can correctly distinguish between an output sequence of the generator and a truly random sequence of the same length with probability significantly greater than 0.5

 Polynomial-time algorithm means, that the running time of the algorithm is bound by a polynomial in the length m of the sequence



# **Pseudo-Random Number Generators (2)**

□ Example:

 A linear congruential generator produces a pseudo-random sequence of numbers y<sub>1</sub>, y<sub>2</sub>, ... According to the linear recurrence

$$y_i = a \times y_{i-1} + b \text{ MOD } q$$

with a, b, q being parameters characterizing the PRBG

 Unfortunately, this generator is predictable even when a, b and q are unknown, and should, therefore, not be used for cryptographic purposes

Network Security, WS 2008/09, Chapter 6



### Random and Pseudo-Random Number Generation (4)

### Definition:

• A PRBG is said to pass the next-bit test, if there is no polynomial-time algorithm which, on input of the first *m* bits of an output sequence *s*, can predict the  $(m + 1)^{st}$  bit  $s_{m+1}$  of the output sequence with probability significantly greater than 0.5

Theorem (universality of the next-bit test):

A PRBG passes the next-bit test

$$\Leftrightarrow$$

it passes all polynomial-time statistical tests

- For the proof, please see section 12.2 in [Sti95a]
- Definition:
  - A PRBG that passes the next-bit test possibly under some plausible but unproved mathematical assumption such as the intractability of the factoring problem for large integers – is called a *cryptographically secure pseudo-random bit generator* (CSPRBG)

7



# Hardware-Based Random Number Generation

- Hardware-based random bit generators are based on physical phenomena, as:
  - elapsed time between emission of particles during radioactive decay,
  - thermal noise from a semiconductor diode or resistor,
  - frequency instability of a free running oscillator,
  - the amount a metal insulator semiconductor capacitor is charged during a fixed period of time,
  - air turbulence within a sealed disk drive which causes random fluctuations in disk drive sector read latencies, and
  - sound from a microphone or video input from a camera
- A hardware-based random bit generator should ideally be enclosed in some tamper-resistant device and thus shielded from possible attackers

#### Network Security, WS 2008/09, Chapter 6



### Software-Based Random Number Generation

- Software-based random bit generators, may be based upon processes as:
  - the system clock,
  - elapsed time between keystrokes or mouse movement,
  - content of input- / output buffers
  - user input, and
  - operating system values such as system load and network statistics
- Ideally, multiple sources of randomness should be "mixed", e.g. by concatenating their values and computing a cryptographic hash value for the combined value, in order to avoid that an attacker might guess the random value
  - If, for example, only the system clock is used as a random source, than an attacker might guess random-numbers obtained from that source of randomness if he knows about when they were generated

Network Security, WS 2008/09, Chapter 6



### **De-skewing**

- □ Consider a random generator that produces biased but uncorrelated bits, e.g. it produces 1's with probability  $p \neq 0.5$  and 0's with probability 1 *p*, where p is unknown but fixed
- The following technique can be used to obtain a random sequence that is uncorrelated and unbiased:
  - The output sequence of the generator is grouped into pairs of bits
  - All pairs 00 and 11 are discarded
  - For each pair 10 the unbiased generator produces a 1 and for each pair 01 it produces a 0
- Another practical (although not provable) de-skewing technique is to pass sequences whose bits are correlated or biased through a cryptographic hash function such as MD-5 or SHA-1



### **Statistical Tests for Random Numbers**

- The following tests allow to check if a generated random or pseudorandom sequence inhibits certain statistical properties:
  - Monobit Test: Are there equally many 1's as 0's?
  - Serial Test (Two-Bit Test): Are there equally many 00-, 01-, 10-, 11-pairs?
  - *Runs Test:* Are the numbers of *runs* (sequences containing only either 0's or 1's) of various lengths as expected for random numbers?
  - Autocorrelation Test: Are there correlations between the sequence and (non-cyclic) shifted versions of it?
  - Maurer's Universal Test: Can the sequence be compressed?
- The above descriptions just give the basic ideas of the tests. For a more detailed and mathematical treatment, please refer to sections 5.4.4 and 5.4.5 in [Men97a]

# Addtional References

 $\mathbf{X}$ 

[Ferg03]	Niels Ferguson, Bruce Schneier, "Practical Cryptography", John Wiley & Sons, 2003
[Men97a]	A. J. Menezes, P. C. Van Oorschot, S. A. Vanstone. Handbook of Applied Cryptography. CRC Press Series on Discrete Mathematics and Its Applications, Hardcover,

- [Sti95a]
   D. R. Stinson. Cryptography: Theory and Practice

   (Discuss to Mathematics and Its Applications)
  - (Discrete Mathematics and Its Applications). Hardcover, 448 pages, CRC Press, 1995.

13

Network Security, WS 2008/09, Chapter 6